

**WATER SPECIALISTS TECHNOLOGIES LLC**

1515 Kastner Place

\*Phone: 407-321-7910

\*Email: info@waterspecialists.biz

Sanford, Florida 32771 USA

\*Fax: 407-321-3098

\*Website: www.waterspecialists.biz

**AF-5 DEFOAMER**

**AF-5** is a low titre point, liquid defoamer designed to control foam in effluent and wastewater discharge systems. In addition, this defoamer controls foam and improves drainage in the white water systems of groundwood and Kraft machines. AF-5 can be pumped through conventional application equipment.. It is manufactured in compliance with the regulations of the Food and Drug Administration, 21 CFR, sections 176.210 and/or 176.170.

**TYPICAL PROPERTIES:**

Appearance: Clear to hazy liquid

Density (pound/gallon): 7.8

Viscosity (80°F, Brookfield RVT #3 spindle, 50 rpm; cP): 1700

Flash Point (Closed Cup, °F): &gt;200

**STORAGE & HANDLING RECOMMENDATIONS:**

AF-5 should be stored above its titre point of 45°F and below 140°F. If the product cools to below its titre point in cold weather it can be used after it is warmed and thoroughly mixed.

Keep container closed and handle with care. Do not pressurize, cut, heat, or weld containers. Empty product containers may contain product residue. Do NOT reuse empty containers without commercial cleaning or reconditioning.

*See Material Safety Data Sheet for further information.*